

Product Information

ISO Class 4 - 5

Cleanroom Class 10 - 100 EU Grade B/C/D

MicroPolx® 4000-HP

80% Polyester / 20% Nylon Sealed Edge Microdenier Cleanroom Wiper

MicroPolx® 4000-HP is a sealed edge cleanroom laundered wiper recommended for ISO Class 4 and above environments composed of polyester and nylon microdenier knitted and minimizes the need for potentially harmful solvents. fiber. It provides superior particle and bacterial removal

without damaging critical surfaces. The wiper's high fiber surface area results in more efficient cleaning performance



Other Microfiber Wipers

- MicroPolx® 2750
- MicroPolx® 1100

Composition and Attributes

- 80 %Polyester / 20% nylon microdenier knitted wiper
- Laundered and packaged in an ISO Class 4 cleanroom
- Ultrasonically sealed edges minimize fiber and particle generation
- Abrasion resistant

Benefits

- Microfiber yarn increases surface area and provides superior wiping efficiency and sorptive performance
- Cleans efficiently with less solvent usage than traditional wipers
- Removes oily soils with little or no solvent required
- Soft hand and non-abrasive sealed-edge are excellent for sensitive or scratch prone surfaces
- Chemically compatible with IPA and other commonly used solvents

Applications

- Semiconductor
- TFT—LCD
- Suited for cleaning precise optical machinery and tools
- Used for cleaning a delicate process in critical cleanrooms
- Compatible with ISO Class 4 (Class 10) cleanroom applications and above
- Irradiated options are available

Value Pack Option

The value pack option provides the same great performance in a more economical bulk packaging format.

www.Berkshire.eu.com Contact: Tel 44 (0) 870 757 2877

enquiries@berkshire.uk.com

Americas	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp



Technical Data:

Attribute		Units	Value	Test Method
Basis Weight		g/m²	259	TAPPI T-410
Caliper		μm	495	TAPPI T-411
Fibers	≥100µm	fibers/cm ²	0.21	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.2
Particles	≥0.5µm	x10³/cm²	10	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.1
Sorbency	Capacity	mL/m²	430	IEST-RP.CC004.3, Sec 8.1 modified / Sec 8.2 modified
	Efficiency	mL/g	1.6	
	Rate	seconds	10	
Non-Volatile Residue	DI Water	g/m²	0.021	IEST-RP.CC004.3, Sec 7.1.2
	IPA	_g/m²	0.24	
Ions	Na ⁺	ppm	0.25	IEST-RP.CC004.3, Sec 7.2.2
	K ⁺	ppm	0.085	
	Ca ⁺⁺	ppm	1.5	
	Mg ⁺⁺	ppm	0.079	
	CI ⁻	ppm	0.45	

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request

Order Information:

Product	Number	Size	Shts/pk	Pks/cs	Style
MicroPolx® 4000-HP	MP4000HP060640	6x6" (15x15cm)	25	40	Stacked
MicroPolx® 4000-HP	MP4000HP090910	9x9" (23x23cm)	50	10	Stacked

Other Berkshire Products



Wipers



Glove Liners



Mop Systems



Documentation Systems



Face Masks



Swabs