

Permovable™

Permovable™, the first easy-to-apply and easy-to-remove floor graphic film that is environmentally safe, durable, non-slip and perfect for any concrete, asphalt or tile surface; floor or wall. Permovable™ is a non-PVC bio degradable self-adhesive graphic film, perfect for quality exterior floor graphics on non-treated surfaces such as streets, parking lots, sidewalks, and more.

Print compatibility

Compatible with (Eco)Solvent and UV-cure inks.



Water
based



(Eco)
solvent



Latex



UV-cure

Physical characteristics

- **Face film:** 50µ glossy white, PVC-free, acrylic, flexible
- **Adhesive:** 38µ clear rubber-base pressure activated
- **Liner:** 170µ polyethylene-two-sides / silicone-one-side, stay-flat liner

- **Expected outdoor life:** 3 months for vehicle traffic, 6 months for foot traffic
- **Water resistance:** Good in non-standing water
- **Non-slip standard:** R11 (DIN 51131)
- **Minimum application temperature:** 10 °C

Features

- PVC-free
- Eco-friendly
- Bio-degradable
- High slip resistance
- Indoor/outdoor use
- Very durable

- No 1:1 competition
- Very easy to install and remove
- Reduces cost of removal
- Unique characteristics
- Ideal for rough surfaces like asphalt, side-walks, etc.

Applications

- Temporary wayfinding
- Sidewalks
- Streets
- Retail advertising
- Concert, fairs
- Sporting events

- Parking lots
- Schools
- Trade show graphics
- Public buildings
- Wedding reception
- Guerilla marketing

Shelf life and environment aspects

The shelf life of this media is 1 year under normal conditions (10°C – 35°C at a relative humidity 30% - 75%). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place in its original packaging.

Important:

Before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.

Sentec International BV

Pascallaan 36
8218 NJ Lelystad
T: +31 (0)320 26 78 26
F: +31 (0)320 26 78 28

www.sentecinternational.com
info@sentecinternational.com