





Product Description

- Two side coated board made from 100% virgin fibres
- Bright, smooth, white surface with clean centre
- Fully recyclable, available as FSC certified
- Ideal alternative to foam boards, foam PVC and other plastic composites

Applications

- Hanging signs
- Free standing displays
- Point of sale displays
- Retail displays and indoor signage

Printing

- Recommended for offset, screen and large format digital printing
- Available in sheet size up to 1700x3600 mm

Conversion

- Excellent is recommended for applications involving: embossing, film and foil lamination, die cutting, varnishing, creasing, perforating, cutting and scoring

Characteristics

Valid from 1 October 2017

Whiteness	9/10
Printability	10/10
Flatness	10/10
Outdoor Use	1/10

Specification

Grammage	Thickness			
g/m2	micron	PT	mm	
370	505	20	0.5	
450	680	27	0.7	
500	800	31	0.8	
620	1000	39	1	
770	1250	49	1.25	
880	1500	59	1.5	
1000	1750	69	1.75	
1100	2000	79	2	
1400	2500	98	2.5	
1600	3000	118	3	
1850	3500	138	3.5	
2140	4000	157	4	
Tolerance				
+/- 10%		+/- 10%		

Oppboga Bruk

- A: Mått-Johans väg 4 SE-732 72 Fellingsbro, Sweden T: +46 (0)581-62 80 00
- **I:** +46 (U)581-62 80 (C **W:** oppboga.com