

Product Information Sheet

Farblöser FH30

Remove all types of ink residues and ink caking on spatulas, counter pressure rollers, ink ducts and any other parts of the printing press, manual application

Excellent cleaning strength.
Free from aromatic hydrocarbons
Very fast evaporation
Could damage unbaked plates

Technical specifications

flashpoint °C	VOC EU	Water miscible	Density (g/ml)	Ink compatibility
<0	100%	partial miscible	appr. 0,76	CONV UV

Application

Can be mixed with up to 30% water for better removal of paperdust.
Blankets: Apply with a cloth or lint free wipe to the blanket. Allow a few seconds for wash to penetrate the ink film, then wipe over with a clean cloth or wipe. Finally rinse surface with clean water.

Storage

This product should be stored in a dry place and at room temperature (5-35°C).

Stability

The shelf life of this product is at least 12 months.

Packaging

1 l bottle
10 l can
20 l can
200 l drum
600 l IBC
1000 l IBC

OTHER • OTHER • OTHER • OTHER • OTHER • OTHER

D/Export: DC DruckChemie GmbH; Wiesenstrasse 10; 72119 Ammerbuch; Tel.: +49 7032 97650 CS: DC s.r.o., DruckChemie CZ; K AMP 1294; 664 34 Kuřim; tel.: +420 541231 911
PL: DC DruckChemie Polska Sp. z o.o.; ul. Spichrzowa 16; 62-200 Gniezno; Fon: +48 61428 6903 FR: Druck Chemie SAS ; 39, Route de Bretten ; 68780 Soppe le Bas ; Fon :
+33389269000 CH : DC DruckChemie Schweiz AG; Schöneich 1; 6265 Roggliswil; Fon: +41 627473030 NL: DC DruckChemie Benelux B.V.; Gerstdijk 7; 5704 RG Helmond;
Tel. +31 492579600 IT: D.C. Druck Chemie Italia srl; Via Tirso, 12; 20098 San Giuliano Milanese (MI); Phone +39 0290420764 ES: Druck Chemie Iberica SL; C/ Tresols nº 11 Bajos;
08850 Gavà (Barcelona) ; Telf: +34 936388606 MEX: Druck Chemie Mexico SA de CV; Aniceto Ortega 817 Planta Baja, Col. del Valle, CP 03100; Mexico D.F.; Phone: +52 55
35368868

