

DATA SHEET 22VK0.100.34000

SIVK

Clear glossy self-adhesive PVC film with paper backing. Suitable for labels, posters, displays and exhibition panels. SIVK is also suitable for glass decoration and shop window graphic advertising or as backlit applied directly on light diffusion boards.

Printing Systems



Rolls

| Art.Number | Width (mm) | Thickness | Length (m) |
|-----------------|------------|-----------|------------|
| 22VK0.100.34000 | 430 | 0.110 mm | 20 |
| 22VK0.100.35900 | 610 | 0.110 mm | 20 |
| 22VK0.100.39000 | 914 | 0.110 mm | 20 |
| 22VK0.100.30500 | 1067 | 0.110 mm | 20 |
| 22VK0.100.32000 | 1270 | 0.110 mm | 20 |
| 22VK0.100.33300 | 1370 | 0.110 mm | 20 |

Technical data

Characteristic



- High brilliance of colours
- Adhesive light
- Universal use

Finish

- Clear glossy
- self-adhesive with paper backing

Specifications

| | |
|---|--|
| Release liner | siliconized paper ~ 0.145 mm |
| Coating Printsides | Power-Gloss®, clear glossy |
| Width (mm) | 430 |
| Thickness base material with inkjet coating | 0.110 mm |
| Core Diameter | 76 mm |
| Adhesion strength | ~ 3.5.N / 25 mm (A.F.E.R.A.), after 24 h ~ 10 N / 25 mm (A.F.E.R.A.) |
| Type of adhesive | polyacrylate dispersion, semipermanent |
| Length (m) | 20 |
| Base Material | calendered monomeric plasticized PVC, 0.100 mm |
| Total thickness | 0.260 mm |
| Packing quantity | 1 roll |

Compatibility

Handling

- Laminating: The printed surface must be protected with foils for cold lamination if it is subject to humidity, sweaty hands, abrasion or any other influences. For a short term outdoor use, SIVK must always be protected with a 5mm overlapping lamination.
- Gluing: SIVK will stick to any solid, smooth surfaces which are dry and free of dirt, grease, silicon etc. Before gluing it is absolutely necessary to check that the surface is appropriate to this aim and that it has been prepared (cleaned) professionally. During gluing the temperature must reach at least 15°C. You can remove SIVK by heating the film's surface with a hot air gun. Then pull it off carefully.

Storage

- Shelf life: 1 year after delivery
- After printing the remaining roll must be removed from the plotter and stored in its closed original packing in a cool and dry environment.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.