

## **Product Information**

Mod.R&S 06 | Rev.4 | Update 10/2017 | Page 1



# P.S. SUBLILT

### Description

PU plotter cut heat seal material with adhesive polyester backing, specifically conceived for low temperature transfers on polyester textiles colored with sublimation inks.

The special structure and processing of the material create a barrier to the dyes, preventing the "migration" effect and maintaining thus unaltered the original color.

Suitable for polyammide or polyester fabrics not treated.

### Usage

- · Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- Remove the support warm or cold

Do not stack or fold the clothings warm in order to avoid staining of the external surface



Average thickness 110 microns



Suggested cutting settings

blade new at 45° pressure 60 gf speed 30 cm/sec



**Transfer settings** 

■ 15 seconds at 130°C (266°F) medium pressure (3-4 bar)

Washing temperature

### Washing

Wait at least **24 hours** from application before washing. Washing resistance up to **40°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning Not suitable for tumble dryer.

The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I



Dry cleaning



Tumble dryer





N.B. All information here contained are based on our experience.
 We recommend to perform a test before starting standard production.
 For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System ISO 9001:2015

www.tuv.com



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations. Updated versions are available on our website www.siser.com For further information, please contact our Sales Office. Thank you

