

FLOOR GRAPHIC LAMINATE (SDG17104, SDG17106, SDG17108)

Product Description	<ul style="list-style-type: none"> ▪ 125mic PVC product coated on one side with a clear solvent acrylic adhesive ▪ 165gsm weight ▪ Gloss level of 6 (85°) ▪ pH- Value of approx. 7 ▪ This product has UV inhibitors ▪ It is for pressure sensitive application ▪ See CERAM test report No (105213)-24241 for verification
Release Liner	<ul style="list-style-type: none"> ▪ White siliconised paper ▪ Release liner is 105gsm
Adhesion Strength	<ul style="list-style-type: none"> ▪ 180° Peel adhesion 1kg/25.4mm (PSTC-1) ▪ 0° Sheer strength 54hr/25.5mm (PSTC-7)
Application Temperature (guide only)	5°c + 40°c
End Use Temperature (guide only)	-20°c to +50°c
Shelf Life	1 year when stored in original packaging at 18°c - 25°c and 40 - 65% Rh
Durability	<ul style="list-style-type: none"> ▪ This product will give excellent performance with outdoor exposure for up to 2 years for vertical applications ▪ This product will give excellent performance with indoor exposure for up to 1 month for horizontal applications ▪ The durability only relates to the film and not the colours of the print
Recommendations	Please ensure the print is perfectly dry before laminating. We suggest to dry the print for at least 24 Hours after printing.