

Via IV Novembre 276, 28882 Crusinallo (VB), Italy

Tel: +39 0323 88 23 00 Fax: +39 0323 64 26 11

Website: www.favini.com

Legal seat - Sede legale

Via Alcide De Gasperi 26, 36028 Rossano Veneto (VI), Italy **Tel:** +39 0424 54 77 11 **Fax admin:** +39 0424 54 06 84

TECHNICAL DATA SHEET

Scheda Tecnica

Mod. PG 7.06-01 rev.3 del 18/03/10

Product	Weight
THE TUBE 1/S	120 g/m ²

Characteristic	Internal Method	Standard Reference	Unit of Measure	Side or Direction	Specific Values	Tolerance 2σ
Substance	PO 301	ISO 536	g/m²	-	120	± 5%
Thickness	PO 303	ISO 534	μm	-	140	± 5%
Absolute Humidity	PO 302	ISO 287	%	-	6,0	± 1
L&W Stiffness (15°/10mm)	PO 323	ISO 2493	mN	MD	200	>
L&W Stiffness (15°/10mm)	PO 323	ISO 2493	mN	CD	100	>

The technical data sheet shall be deemed accepted if not challenged within one month of receipt.

Emission Date	01/10/2010
TDS n°	01TT
Period of Validity	Until next review
R&S Manager	Renato Burba

Our internal methods are based upon the indicated official methods, but could differ in some details. The above data have been agreed in good faith and tested to the best of our knowledge, but we cannot guarantee the results of further reprocessing that are beyond our control.





Via IV Novembre 276, 28882 Crusinallo (VB), Italy

Tel: +39 0323 88 23 00 Fax: +39 0323 64 26 11

Website: www.favini.com

Legal seat - Sede legale

Via Alcide De Gasperi 26, 36028 Rossano Veneto (VI), Italy **Tel:** +39 0424 54 77 11 **Fax admin:** +39 0424 54 06 84

TECHNICAL DATA SHEET

Scheda Tecnica

Mod. PG 7.06-01 rev.3 del 18/03/10

Product	Weight
THE TUBE 2/S	130 g/m ²

Characteristic	Internal Method	Standard Reference	Unit of Measure	Side or Direction	Specific Values	Tolerance 2σ
Substance	PO 301	ISO 536	g/m²	-	130	± 5%
Thickness	PO 303	ISO 534	μm	-	150	± 5%
Absolute Humidity	PO 302	ISO 287	%	-	6,0	± 1
L&W Stiffness (15°/10mm)	PO 323	ISO 2493	mN	MD	220	>
L&W Stiffness (15°/10mm)	PO 323	ISO 2493	mN	CD	110	>

The technical data sheet shall be deemed accepted if not challenged within one month of receipt.

Emission Date	01/10/2010
TDS n°	02TT
Period of Validity	Until next review
R&S Manager	Renato Burba

Our internal methods are based upon the indicated official methods, but could differ in some details. The above data have been agreed in good faith and tested to the best of our knowledge, but we cannot guarantee the results of further reprocessing that are beyond our control.





Via IV Novembre 276, 28882 Crusinallo (VB), Italy

Tel: +39 0323 88 23 00 Fax: +39 0323 64 26 11

Website: www.favini.com

Legal seat - Sede legale

Via Alcide De Gasperi 26, 36028 Rossano Veneto (VI), Italy Tel: +39 0424 54 77 11 Fax admin: +39 0424 54 06 84

TECHNICAL DATA SHEET

Scheda Tecnica

Mod. PG 7.06-01 rev.3 del 18/03/10

Product	Weight
THE TUBE 2/S	260 g/m ²

Characteristic	Internal Method	Standard Reference	Unit of Measure	Side or Direction	Specific Values	Tolerance 2σ
Substance	PO 301	ISO 536	g/m²	-	260	± 5%
Thickness	PO 303	ISO 534	μm	-	300	± 5%
Absolute Humidity	PO 302	ISO 287	%	-	6,0	± 1
L&W Stiffness (15°/50mm)	PO 323	ISO 2493	mN	MD	100	>
L&W Stiffness (15°/50mm)	PO 323	ISO 2493	mN	CD	50	>

The technical data sheet shall be deemed accepted if not challenged within one month of receipt.

Emission Date	01/10/2010
TDS n°	03TT
Period of Validity	Until next review
R&S Manager	Renato Burba

Our internal methods are based upon the indicated official methods, but could differ in some details. The above data have been agreed in good faith and tested to the best of our knowledge, but we cannot guarantee the results of further reprocessing that are beyond our control.





Via IV Novembre 276, 28882 Crusinallo (VB), Italy

Tel: +39 0323 88 23 00 Fax: +39 0323 64 26 11

Website: www.favini.com

Legal seat - Sede legale

Via Alcide De Gasperi 26, 36028 Rossano Veneto (VI), Italy **Tel:** +39 0424 54 77 11 **Fax admin:** +39 0424 54 06 84

TECHNICAL DATA SHEET

Scheda Tecnica

Mod. PG 7.06-01 rev.3 del 18/03/10

Product	Weight
THE TUBE 2/S	340 g/m ²

Characteristic	Internal Method	Standard Reference	Unit of Measure	Side or Direction	Specific Values	Tolerance 2σ
Substance	PO 301	ISO 536	g/m²	-	340	± 5%
Thickness	PO 303	ISO 534	μm	-	390	± 5%
Absolute Humidity	PO 302	ISO 287	%	-	6,0	± 1
L&W Stiffness (15°/50mm)	PO 323	ISO 2493	mN	MD	240	>
L&W Stiffness (15°/50mm)	PO 323	ISO 2493	mN	CD	120	>

The technical data sheet shall be deemed accepted if not challenged within one month of receipt.

Emission Date	01/10/2010
TDS n°	04TT
Period of Validity	Until next review
R&S Manager	Renato Burba

Our internal methods are based upon the indicated official methods, but could differ in some details. The above data have been agreed in good faith and tested to the best of our knowledge, but we cannot guarantee the results of further reprocessing that are beyond our control.