

FOUNT SF 5000

Galaxy Fount SF5000 is a universal fountain additive for sheet fed applications with moderate levels of isopropanol.

Application: Suited for all format of sheetfed presses. Proven performance with all kind of paper stock and with both CtP and conventional plates. It allows low water settings with a stable ink water balance and especially fast clean up properties, also after longer stops.

Fount SF5000 is approved by FOGRA and is fully corrosion protected.

Procedure to use: Drain the circulation system from the old fountain solution and flush with water twice. If the circulation system is heavily polluted with bacteria, ink or paper related substances, perform a system cleaning with Galaxy System Cleaner. After flushing with water, fill the system with the proper water and Fount SF5000. When filled, check pH and conductivity for the correct settings.

Product parameters:	Appearance	Transparent colourless liquid
	Dosage	
	pH @ 3% dosage	4.75 – 5.00 depending on water hardness
	Conductivity	500 µS per 1% dosage
	Specific gravity	1.10 g/cm ³
	Flash point	NA
	Class	NA

Storage conditions: Store at room temperature conditions.

Shelf life: In unopened, original packaging, 12 months from manufacturing date

Packaging: 20kg jerrycan, 200kg PE-Drum, 1000kg IBC. One way packaging.

Version: 01-2012

The information provided in this technical data sheet is to inform our customers. A successful application depends on a variety of different factors. Therefore the advice given in this technical data sheet cannot be used as basis for claims. Our recommendation is where possible to perform tests before entering production runs. We reserve the rights to change product characteristics because of technical progress, amendment of applicable law and mandatory production related needs.