# tesa<sup>®</sup> 4124 Product Information



# Premium Carton Sealing Tape

tesa<sup>®</sup> 4124 is a premium packaging tape based on a highly durable polyvinylchloride-film backing and a strong natural rubber adhesive. The carton sealing tape shows excellent performance on all kinds of cardboards and ensures a safe closure of medium- and also heavy-weight cartons. The tape has a high tensile strength, making it very tearproof. tesa<sup>®</sup> 4124 unwinds smoothly and without noise, which makes it ideal for use in hand dispensers and automatic sealing equipment. The process of cardboard waste recycling will be not disrupted, as confirmed by leading recycling companies and paper mills. tesa<sup>®</sup> 4124 is easily printable and available in white, havana, and transparent.

### Main Application

- Premium packaging tape tesa® 4124 is used for manual and automatic sealing
- The tape is ideal for application on cartons of medium- to heavy-range weight
- The natural rubber adhesive system ensures an excellent adhesiveness to multiple surfaces
- The tape has a strong hold and is extremely tearproof

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Technical Data**

<ul><li>Backing material</li><li>Total thickness</li><li>Type of adhesive</li></ul>	PVC film 65 μm natural rubber		60 % 60 N/cm
Adhesion to <ul> <li>steel</li> </ul>	3.2 N/cm		
<ul><li>Properties</li><li>Automatic application</li><li>Manual application</li></ul>	Yes Yes	<ul><li>Printability</li><li>Low noise unwinding</li></ul>	Yes
Evaluation across relevant tesa® assortment: ●●●● very good  ●●● good  ●● medium  ● low			

#### Additional Information

tesa® 4124 is easy printable. Available colours: white, havana and transparent





# Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit http://l.tesa.com/?ip=04124