

TECHNICAL DATA SHEET

Office Economy Cut-Size

Physical Parameters

	REFERENCE	TARGET	TYPICAL	VALUES
Basis Weight, g/m ²	ISO 536	80.0	76.0	84.0
Thickness, µm	ISO 534	98.0	93.0	103
Stiffness MD, mN	ISO 2493-1		≥ 75	
Stiffness CD, mN	ISO 2493-1		≥ 35	
Tensile MD, kN/m	ISO 1924-2		≥ 4.4	
Bendtsen Roughness, ml/min	ISO 8791-2	220	130	300
Air Permeability, ml/min	ISO 5636-3			≤ 1700
Moisture, %	ISO 287	4.5	4.0	5.0
Formation, #	Internal Method		≥ 25	

Optical Parameters

	REFERENCE	TARGET	TYPICAL	/ALUES
Whiteness, CIE	ISO 11475	136	131	141
Brightness D65, %	ISO 2470-2	101	97.0	105
Opacity, %	ISO 2471	93	≥ 90	

The product specifications provided hereby can be changed on one or more parameters at any time by The Navigator Company

Approved by:

Technical Department: Eng. Vitor Crespo

sgftp / ftp_sheets FTP-PAP-0053 Rev.: 007 - Data: Page: 1 / 1

Printed on: 2017/11/28 16:29:01



QUALITY AND ENVIRONMENTAL INFORMATION

- The Navigator Company's papers are made from Elemental Chlorine Free (ECF) bleached kraft pulp;
- The Navigator Company's papers are produced in a neutral/slightly alkaline papermaking process, therefore considered as "acid free" products which meet the requirements of ISO 9706 standard, "Information and documentation – Paper for documents – Requirements for permanence";
- The Navigator Company's laboratories are accredited according to the ISO 17025 standard;
- Quality, Environmental and Safety Management Systems are certified according to the ISO 9001, ISO 14001 and OHSAS 18001 standards.
- The Navigator Company is chain-of-custody certified according to standards FSC-STD-40-004 and FSC-STD-40-005 (NC-COC-014433/NC-CW-014433) and to standard PEFC ST 2002:2013 (APCER/2007/CDR.0008).