

UV CLEAR FILMS SOLAR CONTROL ANTI-UV



UV CLEAR

Carefully applied to any kind of glazing, UV Clear films are highly effective at absorbing the Sun and the Moon's UV rays (99 % up to 385 nm). This film will protect items and furnishings exposed to light from fading and premature ageing.



TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	0.5 %
Visible light transmission	90 %
Reflection of external visible light	9 %
Reflection of internal visible light	9 %
Total solar energy rejected	14 %
Total solar energy rejected 2*	15 %
Solar ratio :	
Solar energy reflection	9 %
Solar energy absorption	7 %
Solar energy transmission	84 %
Reduction in Solar Glare	13 %
Reduction in Solar Glare g-value	13 % 0.85
g-value	
g-value u-value	
g-value u-value Heat loss Reduction (Winter)	
g-value u-value Heat loss Reduction (Winter) Rejected Infrared (760-2500 nm)	0.85
g-value u-value Heat loss Reduction (Winter) Rejected Infrared (760-2500 nm) Shading coefficient	0.85
g-value u-value Heat loss Reduction (Winter) Rejected Infrared (760-2500 nm) Shading coefficient Installation type : Internal application	0.85
g-value u-value Heat loss Reduction (Winter) Rejected Infrared (760-2500 nm) Shading coefficient Installation type : Internal application Roll length	0.85 0.9 30,5 m

CONSTRUCTION

1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning

- 2. High optical quality polyester
- **3.** Bonding adhesive
- Bohang action of the second sec

MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.

Igepa Belux nv Nijverheidslaan 4 B-9880 Aalter T+3293254545 F+3293254540 www.igepa.be Igepa AnsRue de Bruxelles 174 B-4340 Awans T+3242638960 F+3242638967 www.igepa.be Igepa Belux s.à.r.l. 50, Rue Gabriel Lippmann L-6947 Niederanven T+352486376 F+352496575 www.igepa.lu

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	v
Tinted single pane	\checkmark
Reflective tinted single pane	\checkmark
Clear double pane	\checkmark
Tinted double pane	v
Reflective tinted double pane	\checkmark
Gas-filled double pane - Low E	v
STADIP EXT. clear double pane	\checkmark
STADIP INT. clear double pane	\checkmark

Caution 🗙 Not ✓ Yes recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

